

SERIII-W

Scramble Keypad



Overview

The SERIII scramble keypad is a keypad reader designed to prevent onlookers from detecting the PIN code being entered. The LED's display a randomly allocated set of numbers from 0 to 9. The position of the numbers change every time the keypad is activated. Only the user standing directly in front of the keypad can see the scrambled digits.

Features & Benefits

- Very narrow viewing angle of the lighted, scrambled digits
- The membrane keypad is extremely durable
- Random allocation of digits ensures even wear to the keys
- Individual PIN codes can be up to 9 digits in length
- The SERIII has a weatherproof rating of IP65
- An audible alarm signals when a button is depressed
- Robust polycarbonate enclosure
- The unit is equipped with power-up diagnostics and self-test routine
- The SERIII is provided with Wiegand communication protocol
- Over 3.6 million unique permutations are available
- Terminal connection on the rear of the unit



Check out our Schlage Credential Services



SERIII-W Specifications	
Dimensions (H x W x D)	5.39" x 4.17" x 2.05"
Input voltage	8 - 12 VDC
Input current	500mA max.
Operating temperature	5° F to 122° F
Weight	16.76 oz
Cable distance (Wiegand)	500' with 22AWG 6 conductor stranded with overall shield

Ordering Information

- SERIII-W-GR Scramble keypad (gray)
- SERIII-W-BLK Scramble keypad (black)
- SMK-2-GR Scramble keypad surface mount kit (gray)
- SMK-2-BLK Scramble keypad surface mount kit (black)
- SSMK-2-ADA Scramble keypad surface mount kit (ADA compliant)
- PMK-2-GR Panel mount kit (gray)
- PMK-2-BLK Panel mount kit (black)
- SPMK-2-GR Panel mount kit with steel back box (gray)
- SPMK-2-BLK Panel mount kit with steel back box (black)

Allegion, the Allegion logo, Schlage and the Schlage logo are trademarks of Allegion plc, its subsidiaries and/or affiliates in the United States and other countries. All other trademarks are the property of their respective owners.



